

(19) World Intellectual Property
Organization
International Bureau



16 JUN 2005



(43) International Publication Date
1 July 2004 (01.07.2004)

PCT

(10) International Publication Number
WO 2004/055504 A1

(51) International Patent Classification⁷: **G01N 22/04**,
33/12, G01K 11/06, 13/10, A23B 4/06, 4/07

(74) Agents: **WILSON, Kathryn, S. et al.**; Level 3, Spicer
Building, 329 Durham Street, P.O. Box 2201, Christchurch
(NZ).

(21) International Application Number:
PCT/NZ2003/000279

(22) International Filing Date:
17 December 2003 (17.12.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
522635 17 December 2002 (17.12.2002) NZ

(71) Applicant (for all designated States except US): **AGRE-
SEARCH LIMITED** [NZ/NZ]; East Street, Ruakura
Campus, Hamilton (NZ).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **HILL, Harold,
Keith** [NZ/NZ]; 1845 Kakarama Road, RD 10, Hamilton
(NZ). **LOVATT, Simon, James** [NZ/NZ]; 1/271 River
Road, Hamilton, New Zealand (NZ). **PETCH, Phillip,
Edward** [NZ/NZ]; 68 Chedworth Avenue, Hamilton (NZ).


(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR,
CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD,
GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,
MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU,
SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report

[Continued on next page]

(54) Title: MEASUREMENT APPARATUS AND METHOD



(57) Abstract: An apparatus (1) for measuring the transmission or attenuation of electromagnetic radiation through an object (6), said apparatus including an electromagnetic radiation emitter (2) and detector (3), characterised in that to perform transmission/attenuation measurements, the apparatus is configurable such that said emitter (2) is positioned immediately adjacent the surface of said object (6) and said detector (3) is positioned on an opposing side of the object (6) such that the detector (3) solely, or at least substantially receives electromagnetic radiation transmitted through the object (6) from the emitter (2).

WO 2004/055504 A1